

# Nuttige belasting en druklaag

Lengte (cm)	TL 60/13 en GL 60/13			TL 60/16 en GL 60/16			GL 60/21		
	350 (1)	500 (2)	560 (3)	350 (1)	500 (2)	560 (3)	350 (1)	500 (2)	560 (3)
< 350	-	-	-	-	-	-	-	-	-
360	-	-	4 cm	-	-	-	-	-	-
370	-	4 cm	4 cm	-	-	-	-	-	-
380	-	4 cm	4 cm	-	-	-	-	-	-
390	-	4 cm	4 cm	-	-	-	-	-	-
400	-	4 cm	4 cm	-	-	-	-	-	-
410	-	4 cm	4 cm	-	-	-	-	-	-
420	-	4 cm	4 cm	-	-	-	-	-	-
430	4 cm	4 cm	4 cm	-	-	4 cm	-	-	-
440	4 cm	4 cm	4 cm	-	-	4 cm	-	-	-
450	4 cm	4 cm	5 cm	-	4 cm	4 cm	-	-	-
460	4 cm	5 cm	6 cm	-	4 cm	4 cm	-	-	-
470	4 cm	5 cm	6 cm	-	4 cm	4 cm	-	-	-
480	4 cm	6 cm		-	4 cm	4 cm	-	-	-
490	4 cm	6 cm		-	4 cm	4 cm	-	-	-
500	4 cm	6 cm		-	4 cm	4 cm	-	-	-
510	4 cm			-	4 cm	4 cm	-	-	-
520	4 cm			4 cm	4 cm	5 cm	-	-	-
530	4 cm			4 cm	4 cm	5 cm	-	-	-
540	5 cm			4 cm	4 cm	5 cm	-	-	-
550				4 cm	5 cm	6 cm	-	-	-
560				4 cm	5 cm	6 cm	-	-	-
570				4 cm	5 cm	6 cm	-	-	-
580				4 cm	5 cm	7 cm	-	-	4 cm
590				4 cm	6 cm	7 cm	-	-	4 cm
600				4 cm	6 cm	7 cm	-	4 cm	4 cm
610				4 cm	6 cm	7 cm	-	4 cm	4 cm
620				4 cm	6 cm	7 cm	-	4 cm	4 cm
630				4 cm	7 cm	8 cm	-	4 cm	4 cm
640				4 cm	7 cm	8 cm	-	4 cm	4 cm
650				4 cm	8 cm		-	4 cm	4 cm
660							-	4 cm	4 cm
670							-	4 cm	4 cm
680							-	4 cm	5 cm
690							-	4 cm	5 cm
700							4 cm	4 cm	6 cm
710							4 cm	5 cm	6 cm
720							4 cm	6 cm	7 cm

(1) 350 kg/m<sup>2</sup> = 150 kg/m<sup>2</sup> vloerafwerking + 200 kg/m<sup>2</sup> gebruiksbelasting

(2) 500 kg/m<sup>2</sup> = (1) + niet-dragende scheidingswand van max. 250 kg/m

(3) 560 kg/m<sup>2</sup> = (1) + niet-dragende scheidingswand van max. 360 kg/m